

80 Metaalfe Street Buffalo, New York 14206 716-856-2300/fax 716-856-7115

CRIMSON Suppressor 2218

GENERAL DESCRIPTION:

Crimson Suppressor 2218 is a mineral oil based foam control agent designed to deliver effective control of foam problems at an efficient level. The product works very well as a general purpose foam control agent in inks, coatings, adhesives and a variety of other media.

In industrial processing, Crimson Suppressor 2218 should be used as received or diluted. Water dilutions should be stirred frequently to ensure maximum stability and efficiency. When used in ink, Crimson Suppressor 2218 should be used at dosage rates of 0.1 to 0.3% of the formula weight.

PHYSICAL PROPERTIES:

♦ Appearance: Opaque, amber liquid

◆ Specific Gravity (20°C): .915 g/ml (7.59 lbs./gl)

♦ Flash Point: >150°C

♦ Solubility in Water: Dispersible

APPLICATIONS:

- ♦ Inks and Coatings
- ♦ Adhesives & Glues
- ♦ Paints
- ♦ General Purpose

HANDLING & STORAGE:

STORAGE:

Keep containers tightly closed. Store away from incompatible materials. Do not store in unlabeled or mislabeled containers. Store between 50 and 90°F. Store away from heat. Keep away from all sources of ignition. Do not freeze.

HANDLING:

Avoid contact with eyes, skin, and clothing. Use with adequate ventilation. Do not swallow. Avoid breathing vapors, mists, or dust. Do not eat, drink, or smoke in work area. Wash thoroughly after handling.

^{***} For more detail about product handling & safety info, please refer to the Material Safety Data Sheet ***