



Tech

Technical Data

80 Metcalfe Street  
Buffalo, New York 14206  
716-856-2300/fax 716-856-7115

# CRIMSON Suppressor 2333

## **GENERAL DESCRIPTION:**

Crimson Suppressor 2333 is formulated from a series of synthetic bases that affords the end-user a very efficient defoamer/antifoam with little to no effects that are prevalent with many of the commercially available defoamers. The product is very efficient in releasing entrained air in high viscosity media such as Inks/Coatings, Adhesives and Resins/Polymers.

In industrial processing, Crimson Suppressor 2333 should be used as received. When used in Ink and coatings, Suppressor 2333 should be used at dosage rates of 0.01 to 0.25% of the formula weight. In adhesives, the product should be effective at a dose of 0.05 to 0.3% by weight.

## **PHYSICAL PROPERTIES:**

- ◆ Appearance: Translucent, amber liquid
- ◆ Specific Gravity (20°C): .985 g/ml
- ◆ Flash Point: >200°C
- ◆ Solubility in Water: Dispersible

## **STORAGE & HANDLING:**

### STORAGE:

Keep containers tightly closed. Store away from incompatible materials. Do not store in unlabeled or mislabeled containers. Store between 50 and 90 Deg. F. Store away from heat. Keep away from all sources of ignition. Do not freeze.

### HANDLING:

Avoid contact with eyes, skin, and clothing. Use with adequate ventilation. Do not swallow. Avoid breathing vapors, mists, or dust. Do not eat, drink, or smoke in work area. Wash thoroughly after handling.

## **APPLICATIONS:**

- ◆ Inks and Coatings
  - Waterbased
  - UV/EV
- ◆ Adhesives & Glues
- ◆ Emulsion Polymers

\*\*\*For more detail about product handling & safety info, please refer to the Material Safety Data Sheet\*\*\*